

## DALI PRO PB Coupler

DALI PB Coupler | User interfaces



### Product family features

- DALI pushbutton coupler
- 4 floating inputs

### Product family benefits

- Power supply from DALI
- Standard pushbuttons/switches can be used


### Areas of application

- Classrooms
- Conference rooms
- Suitable for installation in flush-type boxes
- Production and assembly facilities
- Individual offices

## Product datasheet

### Technical data

#### Dimensions & weight



Length	42.0 mm
Width	42.0 mm
Height	20.0 mm
Product weight	22.00 g

#### Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

#### Capabilities

Dimmable	No
Dimming interface	DALI
Number of control outputs	1
Type of installation	Integrated in flush device box

#### Certificates & standards

Type of protection	IP20
--------------------	------

#### Logistical data





Commodity code	853710989900
----------------	--------------

### Equipment / Accessories

- Can be used with DALI Professional or DALIeco light control system

### Download Data

## Product datasheet

File	
	Declarations of conformity 334811_Declaration of conformity &#150; DALI PRO CONT-4 &#150; DALI PRO PB Coupler &#150; DALI PRO Sen
	Installation guide 334697_Technical instructions
	CAD data DALI Pushbutton Coupler CAD IGS
	CAD data 3-dim DALI Pushbutton Coupler CAD Data step

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321496461	DALI PRO PB Coupler	Shipping carton box 20	255 mm x 166 mm x 258 mm	10.92 dm <sup>3</sup>	1033.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.