## WPBC Wireless Push Button Coupler



The Encelium **Wireless Push Button Coupler (WPBC)** enables convenient control of light levels and allows use of any standard push button or switch as an input device to the Encelium X Lighting Control System. The WPBC gives you the flexibility to select the brand, shape, color and size push button or switch preferred for your lighting design. Simply install the WPBC in any standard flush-mount junction box, connect it to mains power, and your selected wall switch.

The WPBC has four field configurable input channels to support a variety of control schemes. Either switches or push buttons can be connected. Each button (input) on the WPBC is field configurable to suit the desired control scheme in the installed space.

This includes commands such as:

- Turn On and Turn Off
- Dim Up and Dim Down
- Recall Scene
- Toggle On/Off
- ► Changing and recall color temperature

Date:	
Company:	
Project:	
, _	

CE

### Works with

Encelium XWireless

#### **Key Features & Benefits**

- Mains powered eliminates the need for battery replacement
- Allows connection and configuration of up to 4 buttons
- Easy and versatile installation and wiring with color coded wires
- >50,000 h lifetime at t<sub>a</sub> = 60°C (140°F)
- Compatible with standard recessed boxes

# ENCELIUM

#### SENSING AND CONTROL

#### Control

Wireless Communication

#### Wireless Range

< 15 m (49.2 ft)</p>

#### ELECTRICAL

#### **Radiated Power**

8 dBm

#### **Nominal Power Consumption**

0.2 to 1 W

#### Nominal Supply Voltage

220 to 240 VAC, 50/60 Hz, 13 mA

#### Number of Inputs

**4** 

#### **Galvanic Insulation Interface**

 Push Button to Mains – basic Insulation (use wires suitable for mains voltage)

#### Connections

- Black: Common
- Blue: Switch Contact 1
- Pink: Switch Contact 2
- Orange: Switch Contact 3
- White: Switch Contact 4

#### **ENVIRONMENTAL**

- **Operating Temperature Range**
- -20° to 60°C (-4° to 140°F)

#### **Relative Humidity**

5% to 85%, non-condensing

#### **Expected Lifetime**

50,000 hours at t<sub>a</sub> = 60°C (140°F)

#### PHYSICAL

#### Dimensions (H x W x D)

49 x 48 X 22 mm (1.9 x 1.8 X 0.87 inches)

#### Weight

40 g (1.4 oz)

#### Housing Color

Gray

#### **Housing Material**

Plastic

#### **Mounting Option**

Wall Box Mount

#### WARRANTY

For warranty details, refer to the full warranty documentation at encelium.com


#### **CERTIFICATIONS & SAFETY**

- Approbations
- CE, FCC

#### **Environmental Suitability**

IP20, Indoor






## Dimensions

## **Ordering Information**


Ordering Code	Description	Approbations	Communication Network
4052899591561	Wireless Push Button Coupler	CE	Wireless

## **Wireless System Overview**



This illustration shows how each component is easily integrated into the Encelium X Lighting Control System.


## Wiring Diagrams



## **Mounting Option**

#### Wall Box Mount

Matching European style face plates are available upon request. Please ask your Encelium Representative for details.



Copyright © 2022 Digital Lumens, Incorporated. All rights reserved. Digital Lumens, the Digital Lumens logo, We Generate Facility Wellness, SiteWorx, LightRules, Lightelligence, Encelium, the Encelium logo, Polaris, GreenBus and any other trademark, service mark, or tradename (collectively "the Marks") are either trademarks or registered trademarks of Digital Lumens, Inc. in the United States and/or other countries, or remain the property of their respective owners that have granted Digital Lumens, Inc. the right and license to use such Marks and/or are used herein as nominative fair use. Due to continuous improvements and innovations, specifications may change without notice.

LMS200 Rev 3 11-22

